



INNOVATION 2011

BUILDING

CONNECTO® CAN10AHP



NEW



Connecto® channel drainage system with polypropylene heel grating.







- New design
- Aesthetic
- Light
- Modular system
- Comply with standards EN1433


BUILDING
SANITARY
ENVIRONMENT



ICONAHP11GB

www.nicoll.fr

	PRODUCT CODE	DESCRIPTION
COMPLETE DRAINAGE CHANNEL 1,00 METER LONG		
NEW ! 	CAN10AHP	1 PP channel + 1 PP heel grating
PVC ACCESSORIES FOR CHANNEL		
	STDR10	Vertical outlet diam. 100 mm
	SVDR10	Vertical outlet diam. 110 mm
	NAT177N	End cap/end or lateral outlet diam. 100 mm
	NAV177N	End cap/end or lateral outlet diam. 110 mm
	FIXCANN	Set of 12 screws and 12 brass inserts



USE

- Enable rainwater drainage
- Universal system for housing and building surroundings

Meet us on

www.caniveau.nicoll.com



DESCRIPTION

- 1 PP channel + 1 heel PP grating
- Load class : A15, for pedestrians and cyclists applications only
- 130 width - 1 m length
- Inlet sectional area : 397 cm²/ml
- Slot size : 7,4 mm

BENEFITS

- Male/female interlocking system : makes installation and watertightness easier
- Realisation on building site of various cases of installations with 3 items only : channel, end cap/end or lateral outlet and vertical outlet
- Universal use of the end cap/end outlet : interlocking on each channel end or on lateral outlet
- Possibility to use lateral or vertical outlet every meter
- Locking system for grating
- Light-weight : makes transport, handling and installation operations easier

INSTALLATION

